

VAGUE Series

Features:

Drawers push-open and soft-close Handleless ergonomic continous drawer Includes fully adjustable drawer sliders Fully finished interiors Includes installation hardware Medium-Density Fiberboard (MDF) construction PVC finish resists moisture and scratches **Notes:**

All sizes of vanities are subject to tolerance, +/- 0.40 inches

Back view for plumbing

22







Side view for plumbing

4













B♦**H**[°]



FURNITURE CHARACTERISTIC



Cabinet in MDF, sides thickness 0,63in, doors and drawers 0,75in, coated in PVC 0,01in waterproof and scratchproof that guarantee long life and reliability. Cabinet with dividers in the upper drawer. Opening type constituted by a milling throat.



Resin washbasin thickness 0,47in impact resistant. Glass washbasin extra-light white thickness 0,59in and resistant to

high temperature and impacts.



Blum push slides guaranteed for 60.000 cycles and allow the adjustment in 2 different positions. Slides used in furnitures allow push opening and soft closing with synchronizer. Slides sides with frosted glass sheet. Hinges used in complementary allow the adjustement in 3 different positions.



It is not necessary to assemble the cabinet (product not in kit).

MIRRORS



Mirroir lighting full-led, guarantee an energy saving of a 80/90% compared to a classic lighting incandescent or halogen and life of about 3/5 times higher.



Unlike normal halogen lamps, do not contain mercury and do not emit harmful UV rays for the health.





Install this product according to the installation guide Spcial site preparation is required.

Wall bracing and Baden Haus supplied hardware are recommended.

The plumbing must be roughed into the plumbing cutout area of the vanity.

Refer to the sink rough-in and the vanity rough-in for proper placement. The water supply and drain lines must be installed before installing the vanity.









Step 1

Pull out completely the drawers and take off from the slide rails.

Step 2

Determine the ideal location of your new vanity. Mark the holes and drill pilot holes in the dry wall.



Step 3

Place the vanity frame on the finished wall and install at the locations drilled with the screws shown in Figure 3:

The long nylon raw for the long screw with nylon washer and metal washer and fix with acorn nut.

The short nylon raw for the short screw.

Fully extend the slide rails out. Place the drawer into the slide rails. To secure drawer, close the drawer until a series of clicks are heard.







Faucet and silicone are not included. All sizes of sinks are subject to tolerance: +/- 0.40 inches (ceramic) and +/- 0.20 inches (glass and resin)

Sink assembly

Install the faucet to the top and drains to the sink. Refer to the faucet and drain manufacturer's instructions. Complete the faucet connections. Run water and check for leaks. Apply a bead of silicone behind the top surface to the finished wall.









Faucet and silicone are not included. All sizes of sinks are subject to tolerance: +/- 0.40 inches (ceramic) and +/- 0.20 inches (glass and resin)

Sink assembly

Install the faucet to the top and drains to the sink. Refer to the faucet and drain manufacturer's instructions. Complete the faucet connections. Run water and check for leaks. Apply a bead of silicone behind the top surface to the finished wall.

RESIN BASIN ART. 50156







Faucet and silicone are not included. All sizes of sinks are subject to tolerance: +/- 0.40 inches (ceramic) and +/- 0.20 inches (glass and resin)

Sink assembly

Install the faucet to the top and drains to the sink. Refer to the faucet and drain manufacturer's instructions. Complete the faucet connections. Run water and check for leaks. Apply a bead of silicone behind the top surface to the finished wall.









Faucet and silicone are not included. All sizes of sinks are subject to tolerance: +/- 0.40 inches (ceramic) and +/- 0.20 inches (glass and resin)

Sink assembly

Install the faucet to the top and drains to the sink. Refer to the faucet and drain manufacturer's instructions. Complete the faucet connections. Run water and check for leaks. Apply a bead of silicone behind the top surface to the finished wall.

GLASS EXTRA-LIGHT BASIN ART. 82412





HIGH CUPBOARD Series Vague - Art. 44322/44323/54837 54857/54850

Features: Includes installation hardy

Includes installation hardware Micro-Density Fiberboard (MDF) construction







Install this product according to the installation guide. Choose fitting hardware according to wall material.







HIGH CUPBOARD





HIGH CUPBOARD Series Vague - Art. 44324/44325/54838/ 54858/54851

Features:

Includes installation hardware Micro-Density Fiberboard (MDF) construction







Install this product according to the installation guide. Choose fitting hardware according to wall material.







HIGH CUPBOARD

